



Φ 350-5



4-Pole

Φ 350-5 系列轴流风机

Φ 350-5 Series Axial Fan





材 质：转子铸铝
Material: Aluminum casting

保护等级: IP54
Protection Class: IP54

绝缘等级: F
Insulation Class: F

轴 承: 免维护滚珠球轴承
Bearing: Maintenance Free Ball Bearing





 B型网罩	 C型网罩	 E型导风筒	 G型网罩	 F型正扣面板	 F型反扣面板
Model No.B	Model No.C	Model No.E	Model No.G	Model No.F0	Model No.F1
YWF.A4S-350S-5BIA00	YWF.A4S-350S-5CIA00	YWF.A4S-350S-5EIA00	YWF.A4S-350S-5GIA00	YWF.A4S-350S-5FIA00	/
YWF.A4T-350S-5BIA00	YWF.A4T-350S-5CIA00	YWF.A4T-350S-5EIA00	YWF.A4T-350S-5GIA00	YWF.A4T-350S-5FIA00	/
YWF.A6S-350S-5BIA00	YWF.A6S-350S-5CIA00	YWF.A6S-350S-5EIA00	YWF.A6S-350S-5GIA00	YWF.A6S-350S-5FIA00	/
YWF.A6T-350S-5BIA00	YWF.A6T-350S-5CIA00	YWF.A6T-350S-5EIA00	YWF.A6T-350S-5GIA00	YWF.A6T-350S-5FIA00	/
YWF.A4S-350S-5BIA05	YWF.A4S-350S-5CIA05	YWF.A4S-350S-5EIA05	YWF.A4S-350S-5GIA05	YWF.A4S-350S-5FIA05	/



Φ 350-5

Model No.D





 D型网罩	电 压 Voltage	频 率 Frequency	电 流 Current	输入功率 Input Power	转 速 Speed	电 容 Capacitor	风 量 Air Flow(OPa)	噪 音 Noise	曲 线 Curve No.	运行温度 Operating Temperature	认 证 Approvals
Model No.D	V	Hz	A	W	RPM	μF	m³/h/CFM	dB(A)	#	Min/Max(°C)	
YWF.A4S-350S-5DIA00	220/230	50	0.60	135	1380	4	2750/1617	58	①	-30/+60	CCC,CE,RoH
		60	0.83	190	1550		3100/1823	60	②		CCC,CE,RoHS,U
YWF.A4T-350S-5DIA00	380/400	50	0.30	135	1360	/	2750/1617	58	①	-30/+60	CCC,CE,RoH
		60	0.34	170	1500		3050/1794	60	②		CCC,CE,RoHS,U
YWF.A6S-350S-5DIA00	220/230	50	0.40	80	950	3	1560/920	53	③	-30/+60	CCC,CE,RoH
		60	0.37	83	1100		1800/1060	54	④		CCC,CE,RoHS,U
YWF.A6T-350S-5DIA00	380/400	50	0.29	70	920	/	1950/1147	53	③	-30/+60	CCC,CE,RoH
		60	0.20	80	1070		2150/1264	54	④		CCC,CE,RoHS,U
YWF.A4S-350S-5DIA05	115/120	50	1.20	135	1350	12	2670/1570	58	①	-30/+60	RoHs
		60	1.60	175	1500		2900/1705	60	②		RoHs.U





Φ 350-5



Model No.B



Model No.C





Model No.G



Φ 350-5

Model No.E



Model No.FO

